



GRAMEGNA®

THE ITALIAN PACKAGING SINCE 1960



TC 55 ME

Semiautomatic packaging
machine

**L-Sealing - integrated tunnel
Sealing bar 540x400 mm**

Description

TC 55 ME is the latest piece of Gramegna® range of semi-automatic modular angular wrapping machines, presenting a monoblock structure that distinguishes it from other proposals. Specifically, the retracting tunnel -equipped with a speed, height and temperature adjustment system- is fully integrated within the welding unit, making the structure of the packaging machine versatile and compact. TC 55 ME presents an enviable series of high-profile technical features, including electronic adjustment of welding time and the presence of Teflon-coated blades, which guarantee the complete absence of fumes. At the same time, this angular wrapping machine provides a complete standard equipment: sealing bar and motorized scrap winder supplied. The STEEL IT version of TC 55 ME is ideal for the needs of the food and pharmaceutical industries. In short, TC 55 ME is a perfect packaging machine for all the companies that Think Big!

Optionals

- Film opening metal sheet
- Stainless steel packaging plate
- Blower
- 2nd tabletop reel support kit
- Roller conveyor lg. 0,5 m stainless steel
- Roller conveyor lg. 1 m
- Sealing belt for food
- Teflon conveyor belt
- Height increase kit - 20 mm
- Height increase kit - 60 mm
- Height increase kit 100 mm
- Small products conveying kit
- Product Guide Kit
- Pedal Kit

Plus

- Efficient and versatile monobloc shrink wrapping machine
- Electronic regulation of the welding time
- Motorized sealing bar and film rewinder
- Sealing bars cooling



GRAMEGNA®

THE ITALIAN PACKAGING SINCE 1960

TC 55 ME

Semiautomatic packaging
machine

**L-Sealing - integrated tunnel
Sealing bar 540x400 mm**

Technical Features

| | | |
|--|------|--|
| Electrical power supply | V | 208 60Hz 3Ph 230V 50Hz 3Ph 400V 50Hz 3Ph 400V 50/60Hz 3Ph |
| Maximum power installed | kW | 6.5 (208V) 6.3 (230-400V) |
| Maximum electrical absorption | • A | 19 (208V) 17 (230V) 10 (400V) |
| Hourly output | p/h | 750 |
| Available dimensions of the sealing bars | • mm | 540x400 |
| Max Reel Dimensions (Ø x width) | • mm | Ø350x600 |
| Max Product Dimensions (length x width x height) | • mm | 500x360x200 |
| Work Surface Height | • mm | 875 |
| Machine dimensions (with the hood open) | • mm | 2780x730x1400 |
| Machine dimensions (with the hood closed) | • mm | 2780x730x1400 |
| Machine packing dimensions | • mm | 2400x900x1510 |
| Weight (Net/Gross) | kg | 287/343 |
| Machine Color | | RAL7035 |
| Packaging plate color | | RAL7035 |
| Sealing Bars Cooling | | standard |
| Film Rewinder | | standard |
| Roller conveyor | | standard (lg. 0,5m) |